

► **INSTALLATION PRODUCTS**

BF 音箱系列

BF-10



10"COAXIAL TWO-WAY SPEAKER SYSTEM 单10"同轴全音域音箱

FREQUENCY RANGE	频率响应	65-18KHz (±3dB)
POWER HANDLING	标称功率	400W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	97dB
NOMINAL DISPERSION	散射角度	80° × 80°
DIMENSIONS (H*W*D)	箱体尺寸	295 × 475 × 302mm
NET WEIGHT	净重	13.5kg

The BF-10 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1.5"compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

BF-12



12"TWO-WAY SPEAKER SYSTEM 单12"两分频全音域音箱

FREQUENCY RANGE	频率响应	65-18KHz (±3dB)
POWER HANDLING	标称功率	480W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	97dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	571 × 398 × 365mm
NET WEIGHT	净重	21kg

The BF-12 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1.5"compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

BF-15



15"TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz (±3dB)
POWER HANDLING	标称功率	500W (2000W)
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	99dB
NOMINAL DISPERSION	散射角度	40° × 90°
DIMENSIONS (H*W*D)	箱体尺寸	720 × 440 × 398mm
NET WEIGHT	净重	32.5kg

The BF-15 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 3"compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.