MPX 系列功率放大器

MPX-1200

MODEL	MPX-1200
OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	 480W+480W 720W+720W
BRIDGED-MONO OPERATION 8 OHMS	1000W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20HZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB (1v) 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS (W×H×D)	482×132×445mm

High reliability and large output

Operating-load auto-recognized
System built-in,ensuring all the
Best optimized-operating status
With different speaker's impedancce
Perfect protection circuit for short
cut,over temperaiure and overload

内置控制系统，保证高可靠性，大功率输出
具有负载自动识别系统，短路识别，不同负载识别，
保证机器在不同的负载下都处于最佳的工作状态
具有完善的保护系统：短路保护、过热保护、超载控制等

MPX-2400

MODEL	MPX-2400
OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	 600W+600W 850W+850W
BRIDGED-MONO OPERATION 8 OHMS	1400W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20KHZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB (1.4v) 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS (W×H×D)	482×132×445mm

High reliability and large output

Operating-load auto-recognized
System built-in,ensuring all the
Best optimized-operating status
With different speaker's impedancce
Perfect protection circuit for short
cut,over temperaiure and overload

内置控制系统，保证高可靠性，大功率输出
具有负载自动识别系统，短路识别，不同负载识别，
保证机器在不同的负载下都处于最佳的工作状态
具有完善的保护系统：短路保护、过热保护、超载控制等