

▶ INSTALLATION PRODUCTS

SF 音箱系列

SF-10



10" TWO-WAY SPEAKER SYSTEM 单10"两分频全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	180W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DIMENSIONS (H*W*D)	箱体尺寸	518 x 320 x 295mm
NET WEIGHT	净重	15.3kg

The SF-10 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker compliment consists of an 10" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 50-100° x 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.

SF-12



12" TWO-WAY SPEAKER SYSTEM 单12"两分频全音域音箱

FREQUENCY RANGE	频率响应	70-20KHz (-10dB)
POWER HANDLING	标称功率	220W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	96dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DRIVER COMPLEMENT	单体组合	12" Cone Driver 1" Dome Tweeter
DIMENSIONS (H*W*D)	箱体尺寸	640 x 362 x 355mm
NET WEIGHT	净重	25kg

The SF-12 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker compliment consists of an 12" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 50-100° x 55° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.

SF-15



15" TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	40-20KHz (-10dB)
POWER HANDLING	标称功率	320W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	97dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DRIVER COMPLEMENT	单体组合	15" Cone Driver 1" Dome Tweeter
DIMENSIONS (H*W*D)	箱体尺寸	728 x 435 x 425mm
NET WEIGHT	净重	32.2kg

The SF-15 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker compliment consists of an 15" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 50-100° x 55° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.