

## PROFESSIONAL POWERED SPEAKER SYSTEM SF 带功放音箱系列

### SF-10P



#### 10" TWO-WAY POWERED SPEAKER SYSTEM 带功放10"全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	150W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DIMENSIONS (H*W*D)	箱体尺寸	440 x 340 x 295mm
NET WEIGHT	净重	13.3kg

The SF-10P is a 2-way full range system with power amp(RMS 150W), computer optimized enclosure. Loudspeaker compliment consists of an 10"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° x 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.

### SF-12P



#### 12" TWO-WAY POWERED SPEAKER SYSTEM 带功放12"全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	200W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DIMENSIONS (H*W*D)	箱体尺寸	640 x 376 x 370mm
NET WEIGHT	净重	27kg

The SF-12P is a 2-way full range system with power amp(RMS 200W), computer optimized enclosure. Loudspeaker compliment consists of an 12"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° x 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.

### SF-15P



#### 15" TWO-WAY POWERED SPEAKER SYSTEM 带功放15"全音域音箱

FREQUENCY RANGE	频率响应	40-20KHz
POWER HANDLING	标称功率	220W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	97dB
NOMINAL DISPERSION	散射角度	50-100° x 55°
DIMENSIONS (H*W*D)	箱体尺寸	630 x 435 x 360mm
NET WEIGHT	净重	21.6kg

The SF-15P is a 2-way full range system with power amp(RMS 220W), computer optimized enclosure. Loudspeaker compliment consists of an 15"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° x 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker compliment.