

INSTALLATION PRODUCTS

RS 音箱系列

RS-122



12" TWO-WAY SPEAKER SYSTEM 单12"两分频全音域音箱

FREQUENCY RANGE	频率响应	35-20KHz
POWER HANDLING	标称功率	400W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	100dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	640 × 435 × 360mm
NET WEIGHT	净重	29.5kg

The RS-122 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

RS-152



15" TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	30-20KHz
POWER HANDLING	标称功率	600W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	101dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	840 × 546 × 440mm
NET WEIGHT	净重	45kg

The RS-152 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

RS-153



DUAL 15" TWO-WAY SPEAKER SYSTEM 双15"两分频全音域音箱

FREQUENCY RANGE	频率响应	30-20KHz
POWER HANDLING	标称功率	1200W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	102dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	1240 × 546 × 440mm
NET WEIGHT	净重	62kg

The RS-153 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 3" compression driver mounted on a 80° × 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.