

POWER AMPLIFIER

CA 系列功率放大器

CA-1900



MODEL	CA-1900
OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	600W+600W 900W+900W
BRIDGED-MONO OPERATION 8 OHMS 4 OHMS	1800W 2150W
TOTAL HARMONIC DISTORTION	≤0.03%
FREQUENCY RESPONSE	20HZ-20KHZ+/-0.1dB
DAMPING FACTOR 8 OHMS	>450
SLEW RATE	>60V/uS
S/N RATIO	>100dB
INPUT SENSITIVITY&IMPEDANCE	0.775v 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS (W x H x D)	482 x 132 x 445mm

High reliability and large output

**Operating-load auto-recognized
System built-in,ensuring all the
Best optimized-operating status
With different speaker's impedancce
Perfect protection circuit for short
cut,over temperaiure and overload**

**内置控制系统，保证高可
靠性,大功率输出
具有负载自动识别系统,短路
识别,不同负载识别,
保证机器在不同的负载下都处
于最佳的工作状态
具有完善的保护系统：短路保
护、过热保护、超载控制等**