

## ▶ **INSTALLATION PRODUCTS**

### **MR音箱系列**

#### **10" TWO-WAY SPEAKER SYSTEM**

##### **单10"两分频全音域音箱**

|                         |      |                   |
|-------------------------|------|-------------------|
| FREQUENCY RANGE         | 频率响应 | 50-20KHz          |
| POWER HANDLING          | 标称功率 | 180W              |
| NOMINAL IMPEDANCE       | 标称阻抗 | 8 ohm             |
| SENSITIVITY ( dB/1m1w ) | 灵敏度  | 95dB              |
| NOMINAL DISPERSION      | 散射角度 | 90° x 60°         |
| DIMENSIONS ( H*W*D )    | 箱体尺寸 | 483 x 343 x 305mm |
| NET WEIGHT              | 净重   | 18kg              |

The MR-10 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 10" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 90° x 60° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



### **MR-12**

#### **12" TWO-WAY SPEAKER SYSTEM**

##### **单12"两分频全音域音箱**

|                         |      |                   |
|-------------------------|------|-------------------|
| FREQUENCY RANGE         | 频率响应 | 40-20KHz          |
| POWER HANDLING          | 标称功率 | 250W              |
| NOMINAL IMPEDANCE       | 标称阻抗 | 8 ohm             |
| SENSITIVITY ( dB/1m1w ) | 灵敏度  | 95dB              |
| NOMINAL DISPERSION      | 散射角度 | 90° x 60°         |
| DIMENSIONS ( H*W*D )    | 箱体尺寸 | 648 x 457 x 349mm |
| NET WEIGHT              | 净重   | 21kg              |

The MR-12 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 90° x 60° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eye bolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



### **MR-15**

#### **15" TWO-WAY SPEAKER SYSTEM**

##### **单15"两分频全音域音箱**

|                         |      |                   |
|-------------------------|------|-------------------|
| FREQUENCY RANGE         | 频率响应 | 35-20KHz          |
| POWER HANDLING          | 标称功率 | 320W              |
| NOMINAL IMPEDANCE       | 标称阻抗 | 8 ohm             |
| SENSITIVITY ( dB/1m1w ) | 灵敏度  | 97dB              |
| NOMINAL DISPERSION      | 散射角度 | 90° x 60°         |
| DIMENSIONS ( H*W*D )    | 箱体尺寸 | 700 x 490 x 395mm |
| NET WEIGHT              | 净重   | 26kg              |

The MR-15 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 90° x 60° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loudspeaker complement.

