

▶ INSTALLATION PRODUCTS

FQ 音箱系列

FQ-15

15" TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	55-18KHz (± 3dB)
POWER HANDLING	标称功率	400W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	99dB
NOMINAL DISPERSION	散射角度	90° × 40°
DIMENSIONS (H*W*D)	箱体尺寸	720 × 465 × 443mm
NET WEIGHT	净重	40kg

The FQ-15 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a 90° × 40° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker compliment.



FQ-151

15" TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	55-18KHz (± 3dB)
POWER HANDLING	标称功率	400W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	99dB
NOMINAL DISPERSION	散射角度	90° × 40°
DIMENSIONS (H*W*D)	箱体尺寸	688 × 463 × 425mm
NET WEIGHT	净重	38.9kg

The FQ-151 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a 90° × 40° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker compliment.



FQ-252

DUAL 15" TWO-WAY SPEAKER SYSTEM 双15"两分频全音域音箱

FREQUENCY RANGE	频率响应	40-20KHz (-10dB)
POWER HANDLING	标称功率	1200W
NOMINAL IMPEDANCE	标称阻抗	4 ohm
SENSITIVITY (dB/1m1w)	灵敏度	101dB
NOMINAL DISPERSION	散射角度	90° × 40°
DRIVER COMPLEMENT	单体组合	15" Cone Driver 1" Dome Tweeter
DIMENSIONS (H*W*D)	箱体尺寸	1240 × 520 × 500mm
NET WEIGHT	净重	64.7kg

The FQ-252 is a 2-way full range system in a computer optimized enclosure. Loudspeaker compliment consists of twin proprietary midrange 15"s, individually loaded into separate subcompartments, and a single 1" compression driver mounted on a 90°×40° horn. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Perforated steel is employed for frontal protection of the loudspeaker compliment.

