



> INSTALLATION PRODUCTS

SA音箱系列

SA-10



10"TWO-WAY SPEAKER SYSTEM 单10"两分频全音域音箱

		,
FREQUENCY RANGE	频率响应	55-20KHz (±3dB)
POWER HANDLING	标称功率	300W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	98dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	500 × 300 × 290mm
NET WEIGHT	净重	16kg

The SA-10 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a 80° x 50° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

SA-12



12"TWO-WAY SPEAKER SYSTEM 单12"两分频全音域音箱

FREQUENCY RANGE	频率响应	45-20KHz (±3dB)
POWER HANDLING	标称功率	400W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	99dB
NOMINAL DISPERSION	散射角度	80° × 50°
DIMENSIONS (H*W*D)	箱体尺寸	605 × 365 × 385mm
NET WEIGHT	净重	27.5kg

The SA-12 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1.5" compression driver mounted on a $80^\circ\times50^\circ$ horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.

SA-15



15"TWO-WAY SPEAKER SYSTEM 单15"两分频全音域音箱

FREQUENCY RANGE	频率响应	40-20KHz (±3dB)
POWER HANDLING	标称功率	500W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (db/1m1w)	灵敏度	99dB
NOMINAL DISPERSION	散射角度	90° × 40°
DIMENSIONS (H*W*D)	箱体尺寸	670 × 410 × 450mm
NET WEIGHT	净重	34kg

The SA-15 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loud speaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 3"compression driver mounted on a $90^\circ \times 40^\circ$ horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 13-ply void-free birch laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loud speaker complement.