

## OMAR OM 系列功率放大器

### OM-550

MODEL	OM-550
OUTPUT POWER: ( PER CHANNEL ) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	500W+500W 720W+720W
BRIDGED-MONO OPERATION 8 OHMS	1000W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20HZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB ( 1v ) 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS ( W x H x D )	482 x 132 x 490mm



High reliability and large output

Operating-load auto-recognized  
System built-in,ensuring all the  
Best optimized-operating status  
With different speaker's impedance  
Perfect protection circuit for short  
cut,over tempaiaire and overload

内置控制系统, 保证高可  
靠性,大功率输出  
具有负载自动识别系统,短路  
识别,不同负载识别,  
保证机器在不同的负载下都处  
于最佳的工作状态  
具有完善的保护系统: 短路保  
护、过热保护、超载控制等

### OM-650

MODEL	OM-650
OUTPUT POWER: ( PER CHANNEL ) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	650W+650W 850W+850W
BRIDGED-MONO OPERATION 8 OHMS	1400W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20KHZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	3dB ( 1.4v ) 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS ( W x H x D )	482 x 132 x 490mm



High reliability and large output

Operating-load auto-recognized  
System built-in,ensuring all the  
Best optimized-operating status  
With different speaker's impedance  
Perfect protection circuit for short  
cut,over tempaiaire and overload

内置控制系统, 保证高可  
靠性,大功率输出  
具有负载自动识别系统,短路  
识别,不同负载识别,  
保证机器在不同的负载下都处  
于最佳的工作状态  
具有完善的保护系统: 短路保  
护、过热保护、超载控制等

### OM-850

MODEL	OM-850
OUTPUT POWER: ( PER CHANNEL ) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	750W+750W 1000W+1000W
BRIDGED-MONO OPERATION 8 OHMS	2100W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20HZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>80V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	3dB ( 1.4v ) 20KΩ
LED INDICATION	SIGNAL,BRIDGE, MONO,CLIP,PROTECT
DIMENSIONS ( W x H x D )	482 x 132 x 490mm



High reliability and large output

Operating-load auto-recognized  
System built-in,ensuring all the  
Best optimized-operating status  
With different speaker's impedance  
Perfect protection circuit for short  
cut,over tempaiaire and overload

内置控制系统, 保证高可  
靠性,大功率输出  
具有负载自动识别系统,短路  
识别,不同负载识别,  
保证机器在不同的负载下都处  
于最佳的工作状态  
具有完善的保护系统: 短路保  
护、过热保护、超载控制等